

AEREA SUD di MICHELE BRUCOLI



VIALE TOMMASO COLUMBO, 17 - 70123 BARI

TEL. 080.5342454 - 080.5346061

FAX 080.5342441

CELL. 3920619352

SITO INTERNET: WWW.AEREASUD.IT E.MAIL: tina@brucoli.it



DIN EN ISO 9001
Certificato N° 71 100 D 107

SEL 16



PARTITA IVA 04249100720 - CODICE FISCALE BRC MHL 55B07 A662T - C.C.I.A.A. 302819 - ALBO AGENTI 6701

Noleggjo Piattaforme Aeree





VIALE TOMMASO COLUMBO, 17 - 70123 BARI
 TEL. 080.5342454 - 080.5346061
 FAX 080.5342441
 CELL. 3920619352
 SITO INTERNET: WWW.AEREA SUD.IT E.MAIL: tina@brucoli.it



SEL 16

16 AX

16 AX



TECHNICAL FEATURES

16 AX

Working height	16
Height to the basket floor	14
Max. side outreach	7,1
Max. capacity in the cage	200
Jib length	no
Max. length	5,3
Max. width	2,1
Stowed machine height	2,4
Wheelbase	2,1
Ground clearance	0,3
Cage dimensions	1,4 X 0,8
Travel speed km/h	0-5
External steering radius	2,8
Turret rotation	360°
Platform rotation	90°+90°
Engine	Hatz 24 kW
Controls	Proportional
Gradeability %	30/60, ..
Tyres	Filled
Hydraulic tank (lt)	70
Fuel tank (lt)	50
Total weight	7400
Active oscillating axle	yes
Max. inclination	5°
Electric circuit	24 V
Starting battery	2 x 80 AH
Max wind speed Km/h	45



Oscillating axle

The AX range machines have an active oscillating axle hydraulically controlled that re-balance through a level valve in the center of the axle. This ensures all 4 wheels remain on the ground during work on uneven ground.



Max load limiting device

The cage has a mechanical load limiting device to avoid overloading of the cage and increase safety.

Two Inclinometers

We take care to ensure the safety of our platforms. Two inclinometers control that the platform does not exceed the 5° gradeability in any part of its structure.



TECHNICAL FEATURES

STANDARD EQUIPMENT

16 AX

Load limiting device	yes
Inclinometer	double
Emergency descent	yes
Travel speed	yes
Hour-meter	yes
Battery charging indicator	no
Lifting and traction hooks	yes
Platform colour	yes
2 sets of operation manuals	yes
CE Certificate	yes

OPTIONALS

16 AX

Engine	3L40 36 Kw HATZ diesel engine	yes
Special equipment	4 WD	yes
	4 WS	yes
	Traction battery bio-energy + pump	yes
	Automatic battery charger	yes
	2 x 220V 2,7 Kw motor pump	yes
	3 x 380V 5,0 Kw motor pump	yes
	24 V emergency motor pump	yes
Platform accessories	Sand anti-penetration kit	yes
	Oscillating axle	std
	Working light	yes
	1000 V insulation working platform	yes
	Road lighting	yes
	Radio intercom system	yes
	Fixed intercom	yes
	Anti-collision kit	yes
	220 V power to the basket	yes
	Air-water outlet in the cage	yes
Tyres	Platform 1,6m + load limiting device	yes
	Platform 1,8m + load limiting device	yes
	Platform 2,0m + load limiting device	yes
Painting	No marking tracks	yes
	Tracked chassis	yes
Painting	Anti-acid painting	n. a.
	Special marine paint	yes